



SWISSCAVE  
KITCHEN

# DATA SHEET SWISSCAVE WIB-88DF-CLASS


## Technical Data

Exterior	
Casing	Black coated steel
Door glazing	Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (double glazed)
Door frame	Frameless (all glass)
Door handle	Anodised, brushed aluminium
Door lock	Yes
Door hinge	Right
Door hinge convertible as option (right to left)	Yes
Product dimensions without door handle (H/W/D)	888 x 590 x 560 mm
Packaging dimensions (H/W/D)	975 x 655 x 640 mm
Interior	
Temperature zones	2
Lighting	All around illumination white, blue, amber (adjustable)
Lighting on/off switch	Yes
Number of shelves total	5
Number of display shelves	0 (optional available)
Shelf material	Beech wood
Telescopic shelves on extendable steel ball bearings	Full extension shelves (80%)
Inside casing	Black PUR
Scope of functions	
Optimal usage	Storing and aging of wine
User interface	2 digital displays (set and actual temp.)
Active carbon filters (ensuring optimal air quality)	Yes
Compressor	JP-HE (high efficient)
Coolant	R600a (environment friendly)
Vibrationfree implementation	Yes
Cooling system	Combined fan and convection cooling
Temperatur Memory Function (Power failure)	Yes
Condensation water container	Yes
Heating	Powerful winter heating function (*In heating mode, temperature and humidity values may vary from the set value)
Acoustic temperature alarm	Yes
Acoustic door alarm	Yes
Feet adjustable to compensate uneven floors	Yes

Performance data	
Bottle capacity	40
Space for oversized bottles (Magnum, 3lt.)	On bottom level
Humidity	Recommendation 50-70%
Actively managed humidity (adjustment range 60-80%)	Nein
Climate classification	SN-T
Volume	100 l
Noise level	42 dB(A) <b>sound-absorbing recommendation</b>
Temperature range lower zone	5 °C - 20 °C
Temperature range upper zone	5 °C - 20 °C
Temperature delta between zones	2 °C

General Information	
Cooler shape	Kitchen-built-in
Maintenance contract (warranty extension)	<b>Recommended</b>
Transport weight	60 kg
Net weight	52 kg
Power consumption per day	0.435 kWh (ca.)
Voltage	220 V / 50 Hz
Cable length	2 m





SWISSCAVE WLI-160DF

A	Green arrow pointing right
B	Green arrow pointing right
C	Light green arrow pointing right
D	Yellow arrow pointing right
E	Orange arrow pointing right
F	Red arrow pointing right
G	Red arrow pointing left

**159 kWh/annum**

42 (with 3 bottle icons)

41dB (with speaker icon)

ABCD

2019/2018