

DATA SHEET SWISSCAVE WL120F

Technical Data

Exterior

Casing	Any colour coated steel
Door glazing	Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (double glazed)
Door frame	
Door handle	
Door lock	Yes
Door hinge	Right
Door hinge convertible as option (right to left)	Yes
Product dimensions without door handle (H/W/D)	831 x 540 x 550 mm
Packaging dimensions (H/W/D)	870 x 590 x 590 mm

Interior

Temperature zones	1
Lighting	Blue ceiling lighting
Lighting on/off switch	Yes
Number of shelves total	6
Shelf material	Beech wood
Telescopic shelves on extendable steel ball bearings	Yes
Inside casing	Black PUR

Scope of functions

Optimal usage	Tempering and storing
User interface	Celsius/Fahrenheit switch
Active carbon filters (ensuring optimal air quality)	No
Compressor	JP-STD
Coolant	R600a (environment friendly)
Vibrationfree implementation	Yes
Cooling system	Combined fan and convection cooling
Temperatur Memory Function (Power failure)	Yes
Condensation water container	Yes
Heating	
Acoustic temperature alarm	Yes
Acoustic door alarm	Yes
Feet adjustable to compensate uneven floors	Yes


Performance data

Humidity	Recommendation 50-70%
Actively managed humidity (adjustment range 60-80%)	
Climate classification	SN-T
Volume	118 l
Noise level	39 dB(A) sound-absorbing recommendation
Temperature range lower zone	5 °C - 20 °C


General Information

Cooler shape	Freestanding
Maintenance contract (warranty extension)	Recommended
Transport weight	35 kg
Net weight	31 kg
Power consumption per day	0,427 kWh (ca.)
Voltage	220 V / 50 Hz
Cable length	2 m






SWISSCAVE WL120F



156 kWh/annum



41
39dB
AB CD

9102/0106