

# DATA SHEET SWISSCAVE CLB-360

## Technical Data

### Exterior

Casing	Black coated steel
Door glazing	Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (double glazed)
Door frame	Filigree edging made of black anodised, brushed aluminium
Door handle	Anodised, brushed aluminium (optionally available)
Door lock	Yes
Door hinge	Right
Door hinge convertible as option (right to left)	Yes
Product dimensions without door handle (H/W/D)	1270 x 595 x 725 mm
Packaging dimensions (H/W/D)	1420 x 645 x 777 mm

### Interior

Temperature zones	1
Lighting	All around illumination white, blue, amber (adjustable)
Lighting on/off switch	Yes
Number of shelves total	5
Number of display shelves	0 (Smart-Rack optional available)
Shelf material	Cedar wood
Telescopic shelves on extendable steel ball bearings	Full extension shelves (80%)
Inside casing	Black PUR

### Scope of functions

Optimal usage	Storage and aging of cigars
User interface	2 digital displays (set and actual temp.)
Active carbon filters (ensuring optimal air quality)	Yes
Compressor	Embraco Fullmotion (speed-controlled)
Coolant	R600a (environment friendly)
Vibrationfree implementation	Yes
Cooling system	Combined fan and convection cooling
Defrost function	Automatic
Temperatur Memory Function (Power failure)	Yes
Condensation water container	Yes
Heating	Powerful winter heating function (*In heating mode, temperature and humidity values may vary from the set value)
Acoustic temperature alarm	Yes
Acoustic door alarm	Yes
Feet adjustable to compensate uneven floors	Yes


### Performance data

Cigar capacity	1800
Humidity	Recommendation 60-80%
Actively managed humidity (adjustment range 60-80%)	Yes
Climate classification	SN-T
Volume	270 l
Noise level	38 dB(A) sound-absorbing recommendation
Temperature range lower zone	12 °C - 23 °C

### General Information

Cooler shape	Free-standing or embeddable with shadow gap
Maintenance contract (warranty extension)	Recommended
Transport weight	75 kg
Net weight	71 kg
Power consumption per day	1.08 kWh (ca.)
Voltage	220 V / 50 Hz
Cable length	2 m





SWISSCAVE AG CLB-360

A

B

C

D

E


F

G


B

---

397 kWh/annum

0,36 m<sup>2</sup>

10°C  
5°C

81023/01/22