


DATA SHEET SWISSCAVE WL355F

Technical Data

| Exterior | |
|---|--|
| Casing | Black coated steel |
| Door glazing | Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (double glazed) |
| Door frame | Filigree edging made of black anodised, brushed aluminium |
| Door handle | Anodised, brushed aluminium (rectangular) (optionally available) |
| Door lock | Yes |
| Door hinge | Right |
| Door hinge convertible as option (right to left) | Yes |
| Product dimensions without door handle (H/W/D) | 1200 x 595 x 710 mm |
| Packaging dimensions (H/W/D) | 1310 x 645 x 740 mm |
| Interior | |
| Temperature zones | 1 |
| Lighting | Blue ceiling lighting |
| Lighting on/off switch | Yes |
| Number of shelves total | 5 |
| Number of display shelves (for perfect wine presentation) | 0 (other shelf types) |
| Number of bottle levels max. | 11 |
| Shelf material | Beech wood |
| Telescopic shelves on extendable steel ball bearings | Yes |
| Inside casing | Black PUR |
| Scope of functions | |
| Optimal usage | Tempering and storing |
| User interface | Celsius/Fahrenheit switch |
| Active carbon filters (ensuring optimal air quality) | Yes |
| Compressor | JP-HE (high efficient) |
| Coolant | R600a (environment friendly) |
| Vibrationfree implementation | Yes |
| Cooling system | Combined fan and convection cooling |
| Defrost function | Automatic |
| Temperatur Memory Function (Power failure) | Yes |
| Condensation water container | Yes |
| Heating | Yes (integrated powerful winter function) |
| Acoustic temperature alarm | Yes |
| Acoustic door alarm | Yes |
| Tilt protection | Yes |
| Feet adjustable to compensate uneven floors | Yes |

| Performance data | |
|---|--|
| Bottle capacity (Bordeaux shape, part of shelves removed) | 130 |
| Bottle capacity (Bordeaux shape, all shelves inserted) | 110 |
| Space for oversized bottles (Magnum, 3lt.) | On top and bottom shelf |
| Humidity | Recommendation 50-70% |
| Climate classification | SN-T |
| Volume | 257 l |
| Noise level | 40 dB(A) sound-absorbing recommendation |
| Temperature range | 5 °C - 20 °C |
| General Information | |
| Cooler shape | Freestanding or built-in with shadow gap |
| Maintenance contract (warranty extension) | Recommended |
| Transport weight | 80 kg |
| Net weight | 76 kg |
| Power consumption per day | 0,427 kWh (ca.) |
| Voltage | 240 V / 50 Hz |
| Cable length | 2 m |





SWISSCAVE WL355F

A **B** **C** **D** **E** **F** **G**

G

156 kWh/annum

111 bottles

40 dB (A) sound power level
AB CD

2019/2021